



Class 1 Amber Magnetic LED Rotating Beacon

#101010

www.ionnic.com



5 Year LED warranty

DESCRIPTION

12 - 36 Volt SAE Class 1 rated aerodynamic low profile amber beacon. Made from polycarbonate lens and epoxy filled base, delivering a rugged shock resistant beacon.

Features 5 different flash patterns, powered by 12 x 3W LED's with included dimming function and 2 simulated rotating options (120FPM). Environmentally sealed (IP67), dust and water resistant. Complies to Australia's heavy vehicle regulations. Magnetic base.

Ideal to suit all heavy duty applications in a commercial or construction environments

TECHNICAL SPECIFICATIONS

Voltage	• 12 - 36 Volt	Mounting	• Magnetic mount, cigarette plug
Current Draw	• 2.8A @ 12 Volt, 1.5A @ 24 Volt	Colour	• Amber
IP Rating	• IP67 rated	Dimensions	• 204mm (D) x 114mm (H)
Lens Material	• Polycarbonate lens	Flash Patterns	• 5 flash patterns
Base Material	• Aluminium, epoxy sealed	Operating Temperature	• -30°C to 50°C
LED Count	• 12 x 3W LED's	Approvals	• ECE R65, SAE J845 Class 1

FLASH PATTERNS

No.	Flash Pattern
1	• Rotating
2	• Simulated rotating
3	• Full flashing (double flash)
4	• Full flashing (quad flash) - default
5	• Full flashing (single flash)

DIMENSIONS

