



Class 1 Green Magnetic LED Rotating Beacon

#101310

www.ionnic.com

DESCRIPTION

12 - 36 Volt Class 1 rated aerodynamic low profile amber beacon. Made from polycarbonate lens and epoxy filled base, delivering a rugged shock resistant beacon.

Features 5 different flash patterns, powered by 12 x 3W LED's with included dimming function and 2 simulated rotating options (120FPM). Environmentally sealed (IP67), dust and water resistant. Complies to Australia's heavy vehicle regulations. Magnetic base.

Ideal to suit all heavy duty applications in a commercial or construction environments



5 Year LED warranty

TECHNICAL SPECIFICATIONS

Voltage	• 12 - 36 Volt	Mounting	• Magnetic mount, cigarette plug
Current Draw	• 2.8A @ 12 Volt	Lead Length	• 4.6 meters
IP Rating	• IP67 rated	Colour	• Green
Lens Material	• Polycarbonate lens	Dimensions	• 204mm (D) x 114mm (H)
Base Material	• Aluminium, epoxy sealed	Flash Patterns	• 5 flash patterns
LED Count	• 12 x 3W LED's	Operating Temperature	• -30°C to 50°C

FLASH PATTERNS

No.	Flash Pattern
1	• Rotating
2	• Simulated rotating
3	• Full flashing (double flash)
4	• Full flashing (quad flash) - default
5	• Full flashing (single flash)

DIMENSIONS

