



**Clipsal T Socket**

#402 Series

by Schneider Electric

www.clipsal.com

**DESCRIPTION**

Surface mount 2 pin Clipsal sockets.

2 Pin parallel rated at 15A at 12 Volt. Max of 32V applications.



**FEATURES**

- Sustainable Green Premium Product
- Mercury free and is REACH regulated (Free of substances of very high concern above the threshold)
- Up to 32 Volt DC applications
- Rated up to 15A at 12 Volt
- RoHS Compliant

**TECHNICAL SPECIFICATIONS**

**Physical Specifications**

Voltage Range	• 32 Volt Max	Dimensions	• 47mm Dia x 28mm Deep
Current Draw	• 15A @ 12 Volt	Fixing Center	• 35-38mm CTC
Material	• Plastic	Socket Shape	• T Shaped (Parallel Socket)

**Sustainability Specifications**

Environmental Disclosure	• EVNPEP1605009	Other Approvals	• AS/NZS 3112 • AS 3100, AS 3109 • AS/NZS 3122:approval number S/1
China RoHS Regulation	• Compliant	Sustainable Offer Status	• Green Premium Product
EU RoHS Regulation	• Compliant	REACH Regulation	• Free of substances of very high concern above the threshold
RoHS Exemption Information	• Yes		
Mercury Free	• Yes		

**Part Numbers**

Part Number.	Colour	Description
402/32GY	• Grey	• Grey Clipsal 2 pin surface mount socket. Rated 15A at 12 Volt
402/32WE	• White	• White Clipsal 2 pin surface mount socket. Rated 15A at 12 Volt