



12 Volt Wet Cell & MF Battery Range

Sold Individually

www.dascosupplygroup.com.au



DESCRIPTION

Battery Configuration



Please contact to our sales staff for a full fitment guide list

TECHNICAL SPECIFICATIONS

Wet Cell Part No.	Maintenance Free Part No.	Reserve Capacity	Cold Cranking Amps Wet / MF	Config	Dimensions (mm) Wet / MF		
					L	W	H
BAT12N24-3	-	-	240	A	185	125	180
BAT12N24-4	-	-	240	B	185	125	180
BATNS40	BATNS40MF	49	320 / 300	B	195	125	220
BATNS40L	BATNS40LMF	49	320 / 300	A	195	125	220
BATNS40ZA	BATNS40ZAMF	49	320 / 300	B	195	125	220
BATNS40ZAL	BATNS40ZALMF	49	320 / 300	A	195	125	220
BATNS60	BATNS60MF	80	350 / 430	A	235	125	225
BATNS60L	BATNS60LMF	80	350 / 430	A	235	125	225
BATNS60A	BATNS60AMF	80	350 / 430	B	235	125	230
BATNS60AL	BATNS60ALMF	80	350 / 430	A	235	125	230
BATN39	-	52	320	A	240	135	200
BATN50	BATN50MF	95	450 / 530	B	238	172	200
BATN51	BATN51MF	95	450 / 530	A	238	172	205
BATN50EF	BATN50EFMF	95	450 / 530	B	224	168	200
BATN51EB	-	95	450 / 530	A	224	168	205
BAT55D23R	BAT55D23RMF	90	450 / 550	B	225	171	220
BAT55D23L	BAT55D23LMF	90	450 / 500	A	225	171	220
BATN52	BATN52MF	113	540 / 630	B	260	170	220
BATN53	BATN53MF	113	540 / 630	A	260	170	220
-	BATN70ZZMF	160	640 / 710	B	300	172	225
BATN70ZZ/L	BATN70ZZLMF	160	640 / 710	A	300	172	225
-	BATN70ZMF	145	730	B	303	172	225
BATN55	BATN55MF	90	440 / 550	A	240	175	175
BATN66	BATN66MF	110	530 / 540	A	280	175	175
BATN88	BATN88MF	165	670 / 750	A	350	175	175
BATN100	BATN100MF	180	700 / 830	A	410	175	235
BATN120	BATN120MF	230	840 / 900	D	510	190	220 / 240
BATN150	BATN150MF	300	950 / 1000	D	510	220	220 / 241
BATN200	BATN200MF	430	1100 / 1150	D	510 / 523	270 / 279	235 / 248