



White  
Lithium Grease  
#CRC5037

www.crcindustries.com.au



## DESCRIPTION

Advanced lubricant and protectant containing an advanced additive package for superior performance and durability in any weather and most temperatures. This versatile grease is designed for light duty applications requiring a long grease life. CRC white lithium grease contains oxidation inhibitors to counter corrosion, and protects with a tough, high viscosity film.

### Applications:

Recommended to lubricate:

- Hinges and latches
- Overhead door tracks
- Open gears and chains
- Cables
- Slide conveyors
- Guide rails
- Cams and pistons
- Excellent as a breakin lubrication for bearings.
- Also used for general purpose lubrication and corrosion protection for machinery, tools, and equipment.

## FEATURES

- Heat and Water Resistant – Provides lasting lubrication and durability under stressful conditions
- Rust & Oxidation Inhibitors – For superior metal protection
- High Purity – White lithium based grease
- Non-conductive.
- MSDS available.

## TECHNICAL SPECIFICATIONS

### Physical Properties (without propellant)

Flash Point	• <-5° C
Odour	• Solvent
Appearance	• Off white grease
Vapour Density	• >Air
Boiling Point	• 59° C (initial)
Solubility	• Negligible in water
% Volatile	• 77%
Specific Gravity	• 0.663
Propellant	• Hydrocarbon

### Special Use Warnings

**Aerosol Cans:** Do not puncture, incinerate or store above 50° C. Exposure to high temperatures may cause can to burst. Do not place in direct sunlight or near any heat source. Aerosol cans will conduct electricity. Keep away from all live electrical sources including battery terminals, solenoids, electrical panels and other electronic components. Failure to observe this warning may result in serious injury from flash fire and/or electrical shock.

**General:** Use only in well ventilated area. Ventilation may be improved by opening a window or door or providing mechanical assistance. Avoid continuous breathing of vapour and spray mist. Avoid contact with the skin and eyes. If ventilation is not adequate, respiratory protection should be worn. For more information regarding short term and long term exposure, review this product's Material Safety Data Sheet.

### Approvals

- MAF Approved (C12) Meat.
- AQIS Approval Category 12 Lubricant Type C.

### Performance Characteristic

Drop Point (ASTM D-2268)	• 177° C
Pour Point	• Minus 17.8° C
Viscosity-Base Oil at 37.8° C	• 1100 SUS
Operating Temperature Range	• Minus 17.8° C to 149° C
Wheel Bearing Leakage (ASTM D-1263)	• 0.10 grams

### Directions

- Shake well before use
- Do not mix greases of different base types
- Use a solvent to remove and clean out traces of incompatible grease before repacking
- Repack according to manufacturer's instructions.

### Disposal

Disposal requirements vary by state and local regulations. All used and unused product should be disposed of in conformance with local, state and commonwealth laws and regulations.



## SAFETY DATA SHEET

### 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

#### 1.1 Product identifier

**Product name** WHITE LITHIUM GREASE (AEROSOL)  
**Synonyms** 5037 - MANUFACTURER'S CODE • CRC WHITE LITHIUM GREASE • WHITE LITHIUM GREASE AEROSOL

#### 1.2 Uses and uses advised against

**Uses** GREASE • LUBRICANT • LUBRICANT - AEROSOL

#### 1.3 Details of the supplier of the product

**Supplier name** CRC INDUSTRIES (AUST) PTY LIMITED  
**Address** 9 Gladstone Road, Castle Hill, NSW, 2154, AUSTRALIA  
**Telephone** (02) 9849 6700  
**Fax** (02) 9680 4914  
**Email** [info.au@crcind.com](mailto:info.au@crcind.com)  
**Website** <http://www.crcindustries.com.au>

#### 1.4 Emergency telephone numbers

**Emergency** 13 11 26 (PIC)

### 2. HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

CLASSIFIED AS HAZARDOUS ACCORDING TO SAFE WORK AUSTRALIA CRITERIA

##### Physical Hazards

Aerosols - Flammable: Category 1  
Aerosols - Pressurised: Category 1

##### Health Hazards

Not classified as a Health Hazard

##### Environmental Hazards

Aquatic Toxicity (Chronic): Category 2

#### 2.2 GHS Label elements

**Signal word** DANGER

##### Pictograms



##### Hazard statements

H222 Extremely flammable aerosol.  
H229 Pressurized container: may burst if heated.  
H411 Toxic to aquatic life with long lasting effects.

##### Prevention statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Do not pierce or burn, even after use.  
P273 Avoid release to the environment.

## PRODUCT NAME WHITE LITHIUM GREASE (AEROSOL)

### Response statements

P391 Collect spillage.

### Storage statements

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C.

### Disposal statements

None allocated.

### 2.3 Other hazards

No information provided.

## 3. COMPOSITION/ INFORMATION ON INGREDIENTS

### 3.1 Substances / Mixtures

Ingredient	CAS Number	EC Number	Content
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (<0.1% W/W BENZENE)	64742-49-0	265-151-9	30 to 60%
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (<3% DMSO EXTRACT)	64742-65-0	265-169-7	10 to 30%
PETROLEUM GASES, LIQUEFIED (<0.1% W/W 1,3-BUTADIENE)	68476-85-7	270-704-2	10 to 30%
PHOSPHORODITHIOIC ACID, O,O-DI-C1-14-ALKYL ESTERS, ZINC SALTS	68649-42-3	272-028-3	1 to 5%
ZINC OXIDE	1314-13-2	215-222-5	<5%
TRIBUTYL BORATE	688-74-4	211-706-5	0.5 to 1.5%

## 4. FIRST AID MEASURES

### 4.1 Description of first aid measures

<b>Eye</b>	If in eyes, hold eyelids apart and flush continuously with running water. Continue flushing until advised to stop by a Poisons Information Centre, a doctor, or for at least 15 minutes.
<b>Inhalation</b>	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or an Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by a Poisons Information Centre or a doctor.
<b>Ingestion</b>	For advice, contact a Poisons Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting. Ingestion is considered unlikely due to product form.
<b>First aid facilities</b>	Normal washroom facilities should be available.

### 4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

### 4.3 Immediate medical attention and special treatment needed

Treat symptomatically.

## 5. FIRE FIGHTING MEASURES

### 5.1 Extinguishing media

Dry agent, carbon dioxide or foam. Prevent contamination of drains and waterways.

### 5.2 Special hazards arising from the substance or mixture

Extremely flammable aerosol. May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition. Aerosol may explode at temperatures exceeding 50°C. Eliminate all ignition sources, including cigarettes, open flames, spark producing switches/tools, heaters, pilot lights, mobile phones, etc when handling. Aerosol cans may explode above 50°C.

### 5.3 Advice for firefighters

Evacuate area and contact emergency services. Toxic gases may be evolved in a fire situation. Remain upwind and notify those downwind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.

## PRODUCT NAME WHITE LITHIUM GREASE (AEROSOL)

### 5.4 Hazchem code

2Y  
2 Fine Water Spray.  
Y Risk of violent reaction or explosion. Wear full fire kit and breathing apparatus. Contain spill and run-off.

## 6. ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear Personal Protective Equipment (PPE) as detailed in section 8 of the SDS. Clear area of all unprotected personnel. Ventilate area where possible.

### 6.2 Environmental precautions

Prevent product from entering drains and waterways.

### 6.3 Methods of cleaning up

Contain spillage, then cover / absorb spill with non-combustible absorbent material (vermiculite, sand, or similar), collect and place in suitable containers for disposal.

### 6.4 Reference to other sections

See Sections 8 and 13 for exposure controls and disposal.

## 7. HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

### 7.2 Conditions for safe storage, including any incompatibilities

Store in a cool (< 50°C), dry, well ventilated area, removed from incompatible substances, heat or ignition sources and foodstuffs. Ensure aerosol containers/ cans are adequately labelled, protected from physical damage and sealed when not in use. Check regularly for damaged/ leaking containers. Large storage areas should have appropriate fire protection systems.

### 7.3 Specific end uses

No information provided.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

### 8.1 Control parameters

#### Exposure standards

Ingredient	Reference	TWA		STEL	
		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
Borate compounds	SWA [Proposed]	--	0.75	--	--
Liquefied petroleum gas (LPG)	SWA [AUS]	1000	1800	1000	1800
Mineral Oil Mist	SWA [AUS]	--	5	--	--
Zinc oxide (dust)	SWA [AUS]	--	10	--	--
Zinc oxide (fume & dust)	SWA [Proposed]	--	2	--	10
Zinc oxide (fume)	SWA [AUS]	--	5	--	10

### Biological limits

No biological limit values have been entered for this product.

### 8.2 Exposure controls

#### Engineering controls

Avoid inhalation. Use in well ventilated areas. Where an inhalation risk exists, mechanical explosion proof extraction ventilation is recommended. Flammable vapours may accumulate in poorly ventilated or confined areas. Vapours are heavier than air and may travel some distance to an ignition source and flash back.

## PRODUCT NAME WHITE LITHIUM GREASE (AEROSOL)

### PPE

<b>Eye / Face</b>	Wear splash-proof goggles.
<b>Hands</b>	Wear nitrile or neoprene gloves.
<b>Body</b>	When using large quantities or where heavy contamination is likely, wear coveralls.
<b>Respiratory</b>	Where an inhalation risk exists, wear a Type A-Class P1 (Organic gases/vapours and Particulate) respirator. Where the boiling point is < 65°C, use an AX filter type.



---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1 Information on basic physical and chemical properties

<b>Appearance</b>	VISCOUS OFF-WHITE LIQUID (AEROSOL DISPENSED)
<b>Odour</b>	SOLVENT ODOUR
<b>Flammability</b>	EXTREMELY FLAMMABLE
<b>Flash point</b>	< -5°C
<b>Boiling point</b>	59°C (Initial)
<b>Melting point</b>	NOT AVAILABLE
<b>Evaporation rate</b>	NOT AVAILABLE
<b>pH</b>	NOT AVAILABLE
<b>Vapour density</b>	> 1 (Air = 1)
<b>Relative density</b>	0.663
<b>Solubility (water)</b>	INSOLUBLE
<b>Vapour pressure</b>	NOT AVAILABLE
<b>Upper explosion limit</b>	NOT AVAILABLE
<b>Lower explosion limit</b>	NOT AVAILABLE
<b>Partition coefficient</b>	NOT AVAILABLE
<b>Autoignition temperature</b>	NOT AVAILABLE
<b>Decomposition temperature</b>	NOT AVAILABLE
<b>Viscosity</b>	NOT AVAILABLE
<b>Explosive properties</b>	NOT AVAILABLE
<b>Oxidising properties</b>	NOT AVAILABLE
<b>Odour threshold</b>	NOT AVAILABLE

### 9.2 Other information

<b>% Volatiles</b>	70 %
--------------------	------

---

## 10. STABILITY AND REACTIVITY

---

### 10.1 Reactivity

Carefully review all information provided in sections 10.2 to 10.6.

### 10.2 Chemical stability

Stable under recommended conditions of storage.

### 10.3 Possibility of hazardous reactions

Polymerization is not expected to occur.

### 10.4 Conditions to avoid

Avoid heat, sparks, open flames and other ignition sources.

### 10.5 Incompatible materials

Incompatible with oxidising agents (e.g. hypochlorites), acids (e.g. nitric acid), alkalis (e.g. sodium hydroxide), heat and ignition sources.

### 10.6 Hazardous decomposition products

May evolve toxic gases (carbon oxides, hydrocarbons) when heated to decomposition.

## 11. TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

**Acute toxicity** This product may have the potential to cause adverse health effects if intentionally misused (e.g. deliberately inhaling contents).

**Information available for the ingredients:**

Ingredient	Oral LD50	Dermal LD50	Inhalation LC50
NAPHTHA (PETROLEUM), HYDROTREATED LIGHT (<0.1% W/W BENZENE)	> 5000 mg/kg (OECD TG 401)	> 2000 mg/kg (OECD TG 402)	> 5610 mg/m <sup>3</sup> (OECD TG 403)
DISTILLATES (PETROLEUM), SOLVENT-DEWAXED HEAVY PARAFFINIC (<3% DMSO EXTRACT)	> 5000 mg/kg (rat).	> 2000 mg/kg (rabbit)	> 5.0 mg/L (rat)
ZINC OXIDE	7950 mg/kg (mouse)	--	2500 mg/m <sup>3</sup> (mouse)
TRIBUTYL BORATE	2150 mg/kg (mouse)	--	--

**Skin** Contact may result in mild irritation, drying and defatting of the skin, rash and dermatitis.

**Eye** Contact may cause discomfort, lacrimation and redness.

**Sensitisation** Not classified as causing skin or respiratory sensitisation.

**Mutagenicity** Not classified as a mutagen.

**Carcinogenicity** Not classified as a carcinogen.

**Reproductive** Not classified as a reproductive toxin.

**STOT - single exposure** Over exposure may result in dizziness and nausea.

**STOT - repeated exposure** Not classified as causing organ damage from repeated exposure.

**Aspiration** Ingestion is considered unlikely due to product form. However, if liquid component is ingested, aspiration into the lungs may cause chemical pneumonitis and pulmonary oedema.

## 12. ECOLOGICAL INFORMATION

### 12.1 Toxicity

Toxic to aquatic life with long lasting effects.

### 12.2 Persistence and degradability

No information provided.

### 12.3 Bioaccumulative potential

No information provided.

### 12.4 Mobility in soil

No information provided.

### 12.5 Other adverse effects

No information provided.

## 13. DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

**Waste disposal** For small amounts, absorb contents with sand or similar and dispose of to an approved landfill site. Do not puncture or incinerate aerosol cans. Contact the manufacturer/supplier for additional information (if required).

**Legislation** Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE

**PRODUCT NAME WHITE LITHIUM GREASE (AEROSOL)**

	LAND TRANSPORT (ADG)	SEA TRANSPORT (IMDG / IMO)	AIR TRANSPORT (IATA / ICAO)
<b>14.1 UN Number</b>	1950	1950	1950
<b>14.2 Proper Shipping Name</b>	AEROSOLS	AEROSOLS	AEROSOLS
<b>14.3 Transport hazard class</b>	2.1	2.1	2.1
<b>14.4 Packing Group</b>	None allocated.	None allocated.	None allocated.

**14.5 Environmental hazards**

Marine Pollutant.

**14.6 Special precautions for user**

<b>Hazchem code</b>	2Y
<b>GTEPG</b>	2D1
<b>EmS</b>	F-D, S-U

**Other information** The environmentally hazardous substance mark is not required when transported in packages of less than 5 kg/L (UN Model Regulations: Special Provision 375; IATA: Special Provision A197; IMDG: Special Provision 969) or less than 500 kg/L by Australian Road and Rail.

**15. REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

<b>Poison schedule</b>	A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP).
<b>Classifications</b>	Safe Work Australia criteria is based on the Globally Harmonised System (GHS) of Classification and Labelling of Chemicals (GHS Revision 7).
<b>Inventory listings</b>	<b>AUSTRALIA: AIIC (Australian Inventory of Industrial Chemicals)</b> All components are listed on AIIC, or are exempt.

**16. OTHER INFORMATION**

**Additional information** AEROSOL CANS may explode at temperatures approaching 50°C.

**RESPIRATORS:** In general the use of respirators should be limited and engineering controls employed to avoid exposure. If respiratory equipment must be worn ensure correct respirator selection and training is undertaken. Remember that some respirators may be extremely uncomfortable when used for long periods. The use of air powered or air supplied respirators should be considered where prolonged or repeated use is necessary.

**PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:**

The recommendation for protective equipment contained within this report is provided as a guide only. Factors such as form of product, method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

**HEALTH EFFECTS FROM EXPOSURE:**

It should be noted that the effects from exposure to this product will depend on several factors including: form of product; frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

**PRODUCT NAME WHITE LITHIUM GREASE (AEROSOL)****Abbreviations**

ACGIH	American Conference of Governmental Industrial Hygienists
CAS #	Chemical Abstract Service number - used to uniquely identify chemical compounds
CNS	Central Nervous System
EC No.	EC No - European Community Number
EMS	Emergency Schedules (Emergency Procedures for Ships Carrying Dangerous Goods)
GHS	Globally Harmonized System
GTEPG	Group Text Emergency Procedure Guide
IARC	International Agency for Research on Cancer
LC50	Lethal Concentration, 50% / Median Lethal Concentration
LD50	Lethal Dose, 50% / Median Lethal Dose
mg/m <sup>3</sup>	Milligrams per Cubic Metre
OEL	Occupational Exposure Limit
pH	relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).
ppm	Parts Per Million
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
SUSMP	Standard for the Uniform Scheduling of Medicines and Poisons
SWA	Safe Work Australia
TLV	Threshold Limit Value
TWA	Time Weighted Average

**Report status**

This document has been compiled by RMT on behalf of the manufacturer, importer or supplier of the product and serves as their Safety Data Sheet ('SDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer, importer or supplier or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer, importer or supplier.

While RMT has taken all due care to include accurate and up-to-date information in this SDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this SDS.

**Prepared by**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: [info@rmtglobal.com](mailto:info@rmtglobal.com)  
Web: [www.rmtglobal.com](http://www.rmtglobal.com)

**[ End of SDS ]**