



## DT Series Straight Backshells

Sold Individually

[www.te.com](http://www.te.com)



### DESCRIPTION

Clips over the end receptacle housing, allows conduit to be easily attached and sealed with heatshrink. Rugged PA66 material, offers a high level of protection to the connector. Perfect for harsh environmental applications where reliable signal circuits are critical to operation performance.



**Operating Temperature** • -55° C to 125° C

**Flammability Rating** • UL 94-HB

### TECHNICAL SPECIFICATIONS

Part Number.	No. of Positions	Tubing Size	Suitable Part No.	Description
DT2PBS-ST	• 2 configurations	• 6mm / 7.5mm / 8.5mm / 10mm	• DT04-2P	• Straight backshell with strain relief to suit 2 pin receptacle
DT2SBS-ST	• 2 configurations		• DT06-2S	• Straight backshell with strain relief to suit 2 pin plug
DT3PBS-ST	• 3 configurations		• DT04-3P	• Straight backshell with strain relief to suit 3 pin receptacle
DT3SBS-ST	• 3 configurations		• DT06-3S	• Straight backshell with strain relief to suit 3 pin plug
DT4PBS-ST	• 4 configurations		• DT04-4P	• Straight backshell with strain relief to suit 4 pin receptacle
DT4SBS-ST	• 4 configurations		• DT06-4S	• Straight backshell with strain relief to suit 4 pin plug
DT6PBS-ST	• 6 configurations	• 8.5mm / 10mm / 13mm	• DT04-6P	• Straight backshell with strain relief to suit 6 pin receptacle
DT6SBS-ST	• 6 configurations		• DT06-6S	• Straight backshell with strain relief to suit 6 pin plug
DT8PBS-ST	• 8 configurations		• DT04-8P	• Straight backshell with strain relief to suit 8 pin receptacle
DT8SBS-ST	• 8 configurations		• DT06-8S	• Straight backshell with strain relief to suit 8 pin plug
DT12PBS-ST	• 12 configurations	• 10mm / 13mm / 17mm	• DT04-12P	• Straight backshell with strain relief to suit 12 pin receptacle
DT12SBS-ST	• 12 configurations		• DT06-12S	• Straight backshell with strain relief to suit 12 pin plug