

QVEE Flexible Braided Sleeving

#ES

AUTOMOTIVE | MINING | MARINE

www.qvee.com.au



Expands up to 300%
of initial diameter size.

DESCRIPTION

Black flexible braided sleeving. Excellent protection from salt, oil and most fuel and solvents. Ideal for use on wiring looms where cables are connected to moving parts.

- Operating temperature range of -70°C to 120°C
- UL224 flammability rating method VW-1

TECHNICAL SPECIFICATIONS

Material	• Braided Polyethelene Terephthalate Monofilaments	Optimal Temperature	• -70°C to 120°C
Flammability	• UL224, method VW-1	Melting Point	• 250°C
Resistant	• Salt, oil, most fuels and solvents	Colour	• Black

PART NUMBERS

Part No.	Normal Diameter Size	Expanded Diameter Size	Roll Size	Description
ES0310	• 3mm	• 10mm	• Cut to length on request	• Black flexible braided sleeving with 10mm expanded diameter
ES0620	• 6mm	• 20mm		• Black flexible braided sleeving with 20mm expanded diameter
ES1230	• 12mm	• 30mm		• Black flexible braided sleeving with 30mm expanded diameter
ES2040	• 20mm	• 40mm		• Black flexible braided sleeving with 40mm expanded diameter
ES2560	• 25mm	• 60mm		• Black flexible braided sleeving with 60mm expanded diameter
ES3070	• 30mm	• 70mm		• Black flexible braided sleeving with 70mm expanded diameter