



HD30 Series Plugs with Cable Clamps


Size 18 Shell

www.te.com




DESCRIPTION

These industry proven connectors are environmentally sealed to IP67 standards. Able to be used in both inline and bulk head applications. Specifically designed for the truck, mining and construction industry.




TECHNICAL SPECIFICATIONS


CONFIGURATIONS




18-6
2 x size 4, 4 x blank




18-8
8 x size 12



18-14
14 x size 16



18-20
2 x size 16, 18 x size 20



18-21
21 x size 20

Amperage Rating:

- Size 20 - 7.5A
- Size 16 - 13A
- Size 12 - 25A
- Size 8 - 60A
- Size 4 - 100A

IP Rating	• IP67 rated	Voltage Rating	• 250 Volt AC / DC
Operating Temperature	• -55 to 125°C	Grommet / Insert Material	• Silicone rubber / unfilled PEI

PART NUMBERS

Part Number.	Dimensions	Terminals	Descriptions
HD36-18-6SN-059	44.97mm x 77.7mm	4 blanks 2 x size 4 sockets	6 circuit plug. Takes 2 x size 4 sockets
HD36-18-8PN-059	42.97mm x 77.7mm	8 x size 12 pins	8 circuit plug. Takes 8 x size 12 pins
HD36-18-8SN-059	42.97mm x 77.7mm	8 x size 12 sockets	8 circuit plug. Takes 8 x size 12 sockets
HD36-18-14PN-059	42.97mm x 77.7mm	14 x size 16 pins	14 circuit plug. Takes 14 x size 16 pins
HD36-18-14PE-059	42.97mm x 77.7mm	14 x size 16 pins	14 circuit plug. Takes 14 x 16 pins. Extra thin walled cable seals
HD36-18-14SN-059	42.97mm x 77.7mm	14 x size 16 sockets	14 circuit plug. Takes 14 x 16 sockets
HD36-18-21SN-059	42.97mm x 77.7mm	21 x size 20 sockets	21 circuit plug. Takes 21 x size 20 sockets