

DELPHI

www.aptiv.com

Packard Weatherpack Male Housing

Sold Individually



DESCRIPTION

Weatherpack connectors Triple ribbed silicone seals & are able to withstand chemicals, fluids and temperatures from -40°C to 125°C. Features a secure locking clip and locking indexing post to prevent mismatching. Rated 20A per circuit.

TECHNICAL SPECIFICATIONS


CONFIGURATIONS




QV12015791
1 x Pin



QV12015792
2 x Pin




QV12015793
3 x Pin



QV12015797
4 x Pin



QV12015798
4 x Pin



QV12015799
6 x Pin

Terminal Cable Size:

- QV12089188 - 3mm auto
- QV12124580 - 4mm auto
- QV12124581 - 5mm auto

Current Rating	• 20 Amps per circuit	Centreline Spacing	• 7.7mm
Cable Range	• 0.5-0.8mm ² (supplied terminals)	Materials	• Contacts: tin plated brass • Cable plug & Seal: Silicone • Housing: PA66
Operating Temperature	• -40°C to 125°C	Approvals	• ELV & RoHS approved
Resistance / Voltage Drop	• <10m @ 20mV / <3.0mV/Amp		

TECHNICAL SPECIFICATIONS

Part Number.	Dimensions	Terminals	Descriptions
QV12015791	14mm x 22mm x 40mm	1 x Socket	1 circuit Packard Weatherpack male housing to take female socket
QV12015792	22mm x 22mm x 40mm	2 x Sockets	2 circuit Packard Weatherpack male housing to take female socket
QV12015793	29mm x 22mm x 40mm	3 x Sockets	3 circuit Packard Weatherpack male housing to take female socket
QV10215797	37mm x 22mm x 40mm	4 x Sockets	4 circuit Packard Weatherpack male housing to take female socket
QV12015798	21mm x 29mm x 41mm	4 x Sockets	Square 4 circuit Packard Weatherpack male housing to take female socket
QV12015799	52mm x 22mm x 40mm	6 x Sockets	6 circuit Packard Weatherpack male housing to take female socket