

QVEE

AUTOMOTIVE | MINING | MARINE

www.qvee.com.au

Heavy Duty Spiral Wrap
Australian Manufactured



DESCRIPTION

Heavy duty, high density polyethylene spiral wrap designed for applications requiring excellent protection of electrical cable, hydraulic hose, air and gas lines. Highly resistant to abrasions and chemicals with a good UV stability. Able to withstand high and low temperatures.



DIMENSIONS

Part No.	Internal Diameter	Wall Thickness	Wrapping Range*	Spool Length
SGX12	9mm	1.4mm	9mm - 13mm	20m
QVSG1620	12mm	2.25mm	12mm - 17mm	
QVSG2020	15mm	2.5mm	16mm - 22mm	
QVSG2520	19mm	2.75mm	20mm - 28mm	
QVSG3220	23mm	3.5mm	24mm - 33mm	
QVSG4020	30.5mm	4.25mm	32mm - 42mm	
QVSG5020	38mm	4.25mm	40mm - 54mm	
QVSG6020	47mm	5.5mm	52mm - 65mm	

*Actual length required: (wrapping range ÷ internal diameter) x cable length

TECHNICAL SPECIFICATIONS

GENERAL SPECIFICATIONS

Material	• High Density Polyethylene (HDPE)
Approvals	• RoHS approved
Minimum Temperature	• -65°C @ short term use
Maximum Temperature	• 100°C @ short term use
Min.Cont Temperature	• -50°C @ continuous use
Max.Cont Temperature	• 80°C @ continuous use

ORGANIC SOLVENTS RESISTANCE

Esters	• Non-Resistant
Ethers	• Non-Resistant
Ketones	• Non-Resistant

FLAMMABILITY

Flame Retardant	• UL94 HB
-----------------	-----------

FUELS / AUTOMOTIVE FLUIDS RESISTANCE

Aliphatic Hydrocarbons	• Non-Resistant
Aromatic Hydrocarbons	• Non-Resistant
Oils / Greases	• Resistant
Brake / Hydraulic Fluid	• Resistant

ACID RESISTANCE

Organic Acids	• Resistant
Inorganic Acids	• Resistant