

**QVEE**  
AUTOMOTIVE | MINING | MARINE

Guard-Shield  
Fibreglass Sleeveings  
Rolls of 25m & 1m

www.qvee.com.au



**DESCRIPTION**

High temperature, silicone coated fibreglass sleeving. A non-alkali sleeving with excellent dielectric resistance. Smooth surface area finish offering high flexibility suited for applications where both low and high temperature protection are required.

-60°C to 200°C withstanding temperature. VW-1 flammability rating. UL & RoHS approved. Supplied in rolls of 25m or 1m sticks.

**TECHNICAL SPECIFICATIONS**

**Features:**

- High withstanding temperature
- Dual layer braiding
- Excellent dielectric resistance
- Suitable for in applications with high voltage installs
- UL & RoHS approved

Dual layer fibreglass sleeving

Sleeving Material	• Fibreglass Fiber
Coating Material	• Silicone
Operating Temperature	• -60°C to 200°C
Flammability Rating	• VW-1
Breakdown Voltage	• 4.0kV
Approvals	• UL, RoHS

**PART NUMBERS**

25m Part No.	1m Part No.	Inside Ø	Wall Thickness @ 4kV	Description
QVSSR004	QVSSR004/1	4mm	0.50mm +/- 0.05	4mm Guard Shield high temperature fibreglass sleeving.
QVSSR006	QVSSR006/1	6mm	0.50mm +/- 0.05	6mm Guard Shield high temperature fibreglass sleeving.
QVSSR008	QVSSR008/1	8mm	0.60mm +/- 0.05	8mm Guard Shield high temperature fibreglass sleeving.
QVSSR010	QVSSR010/1	10mm	0.70mm +/- 0.05	10mm Guard Shield high temperature fibreglass sleeving.
QVSSR012	QVSSR012/1	12mm	0.70mm +/- 0.05	12mm Guard Shield high temperature fibreglass sleeving.
QVSSR015	QVSSR015/1	15mm	0.70mm +/- 0.05	15mm Guard Shield high temperature fibreglass sleeving.
QVSSR020	QVSSR020/1	20mm	0.70mm +/- 0.05	20mm Guard Shield high temperature fibreglass sleeving.